

**PERNI AUTOFISSANTI PER LAMIERE SOTTILI MIN. 0.51MM**  
**SELF-CLINCHING STUDS FOR THIN SHEET METAL MIN. 0.51MM**  
**GOUJONS À SERTIR POUR TÔLES FINES MIN. 0.51MM**  
**EINPRESSGEWINDEBOLZEN FÜR DÜNNBLECH MIN. 0.51MM**  
**PERNOS AUTOINSERTABLES PARA CHAPA FINA MIN. 0.51MM**



Thread size x pitch	B +/-0.4	Hole Size +0.08	L	Min. Sheet Thickness	Minimum distance center-edge
M3 x 0.5	4,5	3	28	0,51	5,6

**MATERIAL: ZINC PLATED STEEL**

sheet hardness max 80 HRB

Disegno di proprietà della Fixi S.r.l. - Non può essere copiato, riprodotto o comunicato a terze persone senza autorizzazione.  
 Drawing owned by Fixi S.r.l.- It cannot be copied, reproduced or communicated to third parties without permission.

**Disegnato da / Designed by:** Ufficio Tecnico  
**Ufficio Tecnico / Tech Office:** tech@fixi.it

10/06/2026

**CODICE PRODOTTO / PART NUMBER**

15CHM3-28SB

**FIXI®**

FIXI s.r.l. Via Bellardi 40/A  
 10146 - Torino (Italy)  
 www.fixi.it - info@fixi.it