

**PERNI AUTOFISSANTI PER LAMIERA A TESTA RIDOTTA**  
**LOW DISPLACEMENT SELF-CLINCHING STUDS FOR SHEET METAL**  
**GOUJONS À SERTIR À TÊTE RÉDUITE POUR TÔLE**  
**EINPRESSGEWINDEBOLZEN FÜR GERINGE RANDABSTÄNDE**  
**PERNOS AUTOINSERTABLES CON CABEZA REDUCIDA PARA CHAPA**



Thread size x pitch	B +/-0.4	Hole Size +0.08	L	Min. Sheet Thickness	Minimum distance center-edge
M3 x 0.5	3,65	3	10	1	3,3

**MATERIAL: ZINC PLATED STEEL**

sheet hardness max 80 HRB

Disegno di proprietà della Fixi S.r.l. - Non può essere copiato, riprodotto o comunicato a terze persone senza autorizzazione.  
 Drawing owned by Fixi S.r.l.- It cannot be copied, reproduced or communicated to third parties without permission.

**Disegnato da / Designed by:** Ufficio Tecnico  
**Ufficio Tecnico / Tech Office:** tech@fixi.it

10/06/2026

**CODICE PRODOTTO / PART NUMBER**

15CHLM3-10

**FIXI®**

FIXI s.r.l. Via Bellardi 40/A  
 10146 - Torino (Italy)  
 www.fixi.it - info@fixi.it