

PERNI AUTOFISSANTI PER LAMIERA A TESTA RIDOTTA
LOW DISPLACEMENT SELF-CLINCHING STUDS FOR SHEET METAL
GOUJONS À SERTIR À TÊTE RÉDUITE POUR TÔLE
EINPRESSGEWINDEBOLZEN FÜR GERINGE RANDABSTÄNDE
PERNOS AUTOINSERTABLES CON CABEZA REDUCIDA PARA CHAPA



Thread size x pitch	B +/-0.4	Hole Size +0.08	L	Min. Sheet Thickness	Minimum distance center-edge
M4 x 0.7	4,65	4	15	1	4,3

MATERIAL: ZINC PLATED STEEL

sheet hardness max 80 HRB

Disegno di proprietà della Fixi S.r.l. - Non può essere copiato, riprodotto o comunicato a terze persone senza autorizzazione.
 Drawing owned by Fixi S.r.l.- It cannot be copied, reproduced or communicated to third parties without permission.

Disegnato da / Designed by: Ufficio Tecnico
Ufficio Tecnico / Tech Office: tech@fixi.it

05/04/2026

CODICE PRODOTTO / PART NUMBER

15CHLM4-15

FIXI®

FIXI s.r.l. Via Bellardi 40/A
 10146 - Torino (Italy)
 www.fixi.it - info@fixi.it