

PERNI AUTOFISSANTI PER ALTE TENUTE DI COPPIA
SELF-CLINCHING STUDS FOR HIGH-STRENGTH APPLICATIONS
GOUJONS À SERTIR HAUTE RÉSISTANCE
EINPRESSGEWINDEBOLZEN FÜR HÖHERE BELASTBARKEIT
PERNOS AUTOINSERTABLES DE ALTA RESISTENCIA



Thread size x pitch	B +/-0.25	Hole Size +0.13	h Max	L	F Max	Min. Sheet Thickness	Minimum distance center-edge
M5 x 0.8	7,8	5	2,7	30	1,14	1,3	10,7

MATERIAL: ZINC PLATED STEEL

sheet hardness max 85 HRB

Disegno di proprietà della Fixi S.r.l. - Non può essere copiato, riprodotto o comunicato a terze persone senza autorizzazione.
 Drawing owned by Fixi S.r.l.- It cannot be copied, reproduced or communicated to third parties without permission.

Disegnato da / Designed by: Ufficio Tecnico
Ufficio Tecnico / Tech Office: tech@fixi.it

23/05/2026

CODICE PRODOTTO / PART NUMBER

15HCHM5-30

FIXI®

FIXI s.r.l. Via Bellardi 40/A
 10146 - Torino (Italy)
 www.fixi.it - info@fixi.it