

**PERNI AUTOFISSANTI PER ALTE TENUTE DI COPPIA**  
**SELF-CLINCHING STUDS FOR HIGH-STRENGTH APPLICATIONS**  
**GOUJONS À SERTIR HAUTE RÉSISTANCE**  
**EINPRESSGEWINDEBOLZEN FÜR HÖHERE BELASTBARKEIT**  
**PERNOS AUTOINSERTABLES DE ALTA RESISTENCIA**



Thread size x pitch	B +/-0.25	Hole Size +0.13	h Max	L	F Max	Min. Sheet Thickness	Minimum distance center-edge
M10 x 1.5	15,7	10	4,1	20	2,29	2,3	13,7

**MATERIAL: ZINC PLATED STEEL**

sheet hardness max 85 HRB

Disegno di proprietà della Fixi S.r.l. - Non può essere copiato, riprodotto o comunicato a terze persone senza autorizzazione.  
 Drawing owned by Fixi S.r.l.- It cannot be copied, reproduced or communicated to third parties without permission.

**Disegnato da / Designed by:** Ufficio Tecnico  
**Ufficio Tecnico / Tech Office:** tech@fixi.it

24/05/2026

**CODICE PRODOTTO / PART NUMBER**

15HCHM10-20

**FIXI®**

FIXI s.r.l. Via Bellardi 40/A  
 10146 - Torino (Italy)  
 www.fixi.it - info@fixi.it