
INSERTI FILETTATI CILINDRICI GODRONATI - TESTA SVASATA KNURLED CYLINDRICAL THREADED INSERTS - COUNTERSUNK HEAD INSERTS FILETÉS CRANTÉS CYLINDRIQUES- TÊTE FRAISÉE BLINDNIETMUTTERN RUNDSCHAFT GERÄNDELT - SENKKOPF TUERCAS REMACHABLES CILINDRICAS ESTRIADAS - CABEZA AVELLANADA





	S	D	253	Т	K	L	1	De
	GRIP	+0,07/-0,1	+0,1/-0	+/-0,5	+/-0,15	+/-0,5	~	Nm
M12	1.5 - 4.5	15.9	16	19	1.7	24	14	50

MATERIALE: ACCIAIO INOX A2



COPPIA DI SERRAGGIO MASSIMA (Nm) 50



CARICO DI TRAZIONE SUL FILETTO (N) 34000



TENUTA ALLA COPPIA DIRETTA (Nm) 24



VALORI AL TAGLIO (N) 6500

Disegno di proprietà della Fixi S.r.l. - Non può essere copiato, riprodotto o comunicato a terze persone senza autorizzazione. Drawing owned by Fixi S.r.l. - It cannot be copied, reproduced or communicated to third parties without permission.

Disegnato da / Designed by: Ufficio Tecnico Ufficio Tecnico / Tech Office: tech@fixi.it

17/09/2025

CODICE PRODOTTO / PART NUMBER

85IXITSGM12C16

